KombiSIGN 50 / Bulb Bulb 5W BA15D 12V



Part No.: 955.840.34

| MECHANICAL DATA | |
|------------------------------|--------------------------------|
| Height | 42 mm |
| Diameter | 16 mm |
| Housing colour | Silver |
| Weight with packaging | 8 g |
| Product weight | 8 g |
| ELECTRICAL DATA | |
| Operating voltage | 12V |
| Operating voltage frequency | 50Hz |
| Operating voltage tolerance | +/- 10% |
| Rated operational voltage | 12 VDC |
| Rated operational current | 417 mA |
| Rated inrush current | 4.170 mA |
| Power illuminant | 5 W |
| OPTICAL DATA | |
| Lamp fitting/socket | BA15d |
| APPROVAL DATA | |
| Conforms with CE | No |
| Conforms with RoHS directive | Fulfills substance restriction |
| WEEE | No |
| Conforms with ATEX-directive | No |
| Conforms with CCC | No |
| Conforms with FCC | No |
| Conforms with IC | No |
| EAC certificate available | No |
| Conforms with AS-I | No |
| ICAO Certification | No |
| Conforms with DNV | No |
| Conforms with RoHS CN | No |

Pror additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.