

Permanent Light 815 / Bulb

**Bulb 7W BA15D 48V**



**Part No.:** 955.015.36

## MECHANICAL DATA

|                       |        |
|-----------------------|--------|
| Height                | 54 mm  |
| Diameter              | 16 mm  |
| Housing colour        | Silver |
| Weight with packaging | 9 g    |
| Product weight        | 9 g    |

## ELECTRICAL DATA

|                             |          |
|-----------------------------|----------|
| Operating voltage           | 48V      |
| Operating voltage frequency | 50Hz     |
| Operating voltage tolerance | +/- 10%  |
| Rated operational voltage   | 48 VAC   |
| Rated operational current   | 146 mA   |
| Rated inrush current        | 1.460 mA |
| Power illuminant            | 7 W      |

## OPTICAL DATA

|                     |       |
|---------------------|-------|
| Lamp fitting/socket | BA15d |
|---------------------|-------|

## APPROVAL DATA

|                              |                                |
|------------------------------|--------------------------------|
| Conforms with CE             | No                             |
| Conforms with RoHS directive | Fulfills substance restriction |
| WEEE                         | No                             |
| Conforms with ATEX-directive | No                             |
| Conforms with CCC            | No                             |
| Conforms with FCC            | No                             |
| Conforms with IC             | No                             |
| EAC certificate available    | No                             |
| Conforms with AS-I           | No                             |
| ICAO Certification           | No                             |
| Conforms with DNV            | No                             |
| Conforms with RoHS CN        | No                             |



For additional installation and mounting information, refer to the appropriate user guide at [www.werma.com](http://www.werma.com). This printed copy is for information only and is subject to alteration.